



Slovenski inštitut za
kakovost in meroslovje
Slovenian Institute of
Quality and Metrology

Poročilo o preskusu / Test Report

Št. / No.:

T211-0160/10

Datum / Date:

2010-04-19

Proizvod / Product Surface mounted installation box Type: N24C and N24D	Listov / Pages 2
Naročnik / Applicant TEHNOPLAST d.o.o. Zdravka Jekiča 119 22305 Stari Banovci, Serbia	Vrsta preskusa / Test procedure IK08 test
Proizvajalec / Manufacturer TEHNOPLAST d.o.o. Zdravka Jekiča 119 22305 Stari Banovci, Serbia	Št. Merjencev / No. of Items tested 2
Blagovna znamka / Trade Mark TEHNOPLAST	Mapa predmeta št. / Subject File No. C20100572
Standardi – predpisi / Standards - regulations SIST EN 50102:2001 + A1:2001 (EN 50102:1995 + A1:1998)	Kraj preskusa / Place of test SIQ, Ljubljana
	Opomba / Remark /

Zaključek / Conclusion

Tested product complies with the requirements of stated standards for IK08 classification.

The test results relate only to the items tested.

Date of receipt of test items: 2010-03-15

Date of performance of tests: 2010-03-30

Odgovoren za preskušanje / Responsible for the test

Tibor Kokelj

Vodja področja / Department Manager

Tomaž Knez

Slovenski inštitut za kakovost in meroslovje • Slovenian Institute of Quality and Metrology
Tržaška cesta 2, SI-1000 Ljubljana, Slovenia • t: +386 1 4778 100 • f: +386 1 4778 444 • e: info@siq.si • http://www.siq.si
Razmnoževanje poročila, razen v celoti, ni dovoljeno / This report shall not be reproduced except in full

1. Conditions of test:

- Installation boxes were preconditioned in refrigerator at -25°C for 2 hours (specification from EN 60670-1:2005 and declaration of lower temperature range by manufacturer).
- Vertical hammer according to Figure A.3 of EN 50102:1995 + A1:1998 was used for test.
- Five blows were applied evenly to each of exposed surfaces of the installation boxes.

2. Test results:

- After applying blows, surfaces of installation boxes Type N24C and N24D were examined for damage. There was no visible cracks or indentations found.

3. Conclusion

Installation boxes Type N24C and N24D comply with requirements of IK08 test at -25°C .

4. Photos

